(12) INTERNATIONAL AFTER CATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 19 February 2004 (19.02.2004)

PCT

(10) International Publication Number WO 2004/014202 A1

(51) International Patent Classification⁷: 19/22, 19/12

A47G 21/18,

(21) International Application Number:

PCT/AU2003/001016

(22) International Filing Date: 12 August 2003 (12.08.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2002950725

12 August 2002 (12.08.2002) AU

(71) Applicants and

- (72) Inventors: CLIFTON, Peter [AU/AU]; 35 Day Street, WYOMING, New South Wales 2250 (AU). CHAMULKO, Craig, Dean [AU/AU]; 71 Dahlia Street, GREYSTANES, New South Wales 2145 (AU).
- (74) Agent: GRIFFITH HACK; GPO Box 4164, SYDNEY, New South Wales 2001 (AU).


- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A DRINKING APPARATUS



(57) Abstract: A drinking apparatus (10) including a container (12) having a lid (14) and defining an internal cavity for holding a body of liquid; a valve element (18) operates in conjunction with an opening on the container (12) and is operable between an open condition and a closed condition; the valve element (18) is biased to the closed condition wherein the apparatus completely encapsulates the internal cavity to thereby prevent substances from being introduced to the cavity; and removal of the lid (14) from the container results in an indication that the apparatus has been tampered with.

A DRINKING APPARATUS

Technical Field

This invention relates to a drinking apparatus.

5

10

15

20

Background to the Invention

When a drink is kept in a container such as a cup or glass, there exists the risk that the drink may be deliberately contaminated by a person introducing a substance into the cup or glass such as by dropping the substance into the upper opening of the cup or glass when the drink is left unattended. This practice is colloquially known as "spiking a drink". Drinks have reportedly been spiked with substances including pharmaceutical substances, drugs or poisons in solid, liquid or powder form and even alcohol.

The effects on a person of having their drink spiked depend largely on the substance involved. A person may introduce a toxic substance to deliberately harm or confuse the user, or may introduce a drug in order to take advantage of the user when they are under the effects of the drug.

Summary of the Invention

In a first aspect the present invention provides a drinking apparatus including a container having a lid and defining an internal cavity for holding a body of liquid; a valve element operates in conjunction with an opening on the container and is moveable between an open condition and a closed condition; the valve element is biased to the closed condition wherein the apparatus completely encapsulates the internal cavity to thereby prevent substances from being introduced to the cavity; and

25

removal of the lid from the container results in an indication that the apparatus has been tampered with.

In this way, the apparatus keeps a drink in the container and prevents substances from being added to the drink. If the lid of the container is removed in an attempt to introduce a substance the indication of tampering alerts a user that the apparatus has been tampered with.

The indication that the apparatus has been tampered with may include damage to either the lid or the cup.

The action of drawing liquid through the opening may cause the valve element to move to the open condition.

The valve element may be biased to the closed condition by gravity.

The container may be a cup.

The lid may be arranged to be snap fitted to the container.

The lid and container may fit together closely to resist removal of the lid by use of a leveraging tool.

The opening may be the bore of a straw.

The straw may be marked on its outer surface in the region of the valve element. This means that removal of that region of the straw is apparent to a user.

The region of the straw may be marked by colouring the region. The marking may be luminous or flourescent.

The valve element may be luminous or fluorescent.

Brief Description of the Drawings

An embodiment of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

Figure 1 is a plan view of an embodiment of a drinking apparatus according to the present invention;

15

20

Figure 2 is a cross section view along the line A-A of Figure 1;

Figure 3 is an enlarged detail view of region C of Figure 1;

5 Figure 4 is an enlarged detail view of region B of Figure 2 with the valve element in the open position;

Figure 5 is an enlarged detail view of region B of Figure 2 with the valve element in the closed position;

Figures 6, 7 and 8 are top, side and plan views respectively of the valve element of Figure 2;

Figure 9 is a top view of the straw and valve element according to an alternative embodiment of the invention;

Figures 10 is a cross section view along the line D-D of Figure 9 showing installation of the valve element;

Figure 11 is a cross section view along the line D-D of Figure 9 showing the valve element in the open position; and

Figure 12 is a cross section view along the line D-D of Figure 9 showing the valve element in the closed position.

Detailed Description of the Preferred Embodiment

Referring to Figures 1 and 2, a drinking apparatus 10 is shown including a container in the form of cup 12 and a 25 lid 14. Container 12 and lid 14 define an internal cavity 11 for holding a body of liquid such as a drink. The apparatus includes an opening in the form of the bore 15 of straw 16. Straw 16 is retained with lid 14 such as by being integrally formed with lid 14 by moulding the straw 16 and lid 14 as one component. Straw 16 includes a valve element in the form of plug 18. Plug 18 includes through holes 20.

To use the apparatus, a drink is poured into cup 12

10

15

whilst lid 14 is not engaged with the cup. When the drink has been poured, lid 14 is snap fitted to cup 12. Lugs 22 on lid 14 engage under annular and inwardly directed projection 24 on the inner surface of cup 12. After engaging lid 14 and cup 12, they cannot be separated without damaging either the lid 14 or the cup 12. This provides a tamper evident mechanism to alert a user to the possibility that the container has been interfered with and possibly has had a foreign substance introduced into it.

Referring to Figure 3, lid 14 and cup 12 engage with a close fit. This prevents a levering tool, such as a knife blade or screwdriver, from being inserted between the lid 14 and cup 12 for the purpose of prising off lid 14.

Substances are prevented from being introduced to the container through bore 15 by valve element 18. Referring to Figure 4, when a user sucks on straw 16 the fluid that rises up bore 15 causes plug 18 to move to an open 20 position. At other times, plug 18 is biased by the force of gravity to the closed position shown in Figure 5. In this position, plug 18 rests on valve seat 19. Valve seat 19 blocks the through holes 20 in plug 18, thus preventing any foreign substances from by-passing plug 18 to enter cavity 11.

Annular projection 21 prevents plug 18 from coming out of the upper end of straw 16. Annular projection 21 may be formed by applying heat and pressure to the straw to deform the straw.

Referring to Figures 9 to 12 an alternative embodiment of a valve element of a drinking apparatus according to the invention is shown. In this embodiment the valve element is in the form of a sphere 31. The

15

30

underside of valve seat 19 includes a lead-in taper 26 which assist with insertion of sphere 31 into the straw by use of mandrel tool 28. In the open position, sphere 31 is prevented from exiting upper end of straw 16 by covered end 30. Liquid may flow out of straw 16 through holes 32. In the closed position valve seat 19 prevents substances from by-passing the sphere and entering the container.

The outside of straw 16 is coloured by application of a fluorescent or luminous non toxic dye (not shown) in the vicinity of sphere 31. The fluorescent or luminous colouring improves visibility in low light or dark conditions. If the straw 16 is cut to remove the region of the straw that houses the valve element, this will be readily apparent to a user because they will know to expect to see the coloured portion on the straw of an apparatus that has not been tampered with. Similarly, the valve element may be made luminous or fluorescent to alert a user if the valve element is missing.

In another embodiment, lid 14 is formed with a

concave region on its upper surface which takes up all or
part of the upper surface. This provides a catchment area
for any liquid substance that is placed on top of lid 14
and helps to prevent that liquid from running off lid 14
to enter the apparatus at the join between cup 12 and lid

14.

All parts of the apparatus are formed from a clear, recyclable plastic that is difficult to penetrate with a hypodermic needle. A suitable plastic is Polypropylene Grade, wide spec. 4-14 Thermoplastic (TPE) or equivalent, talc filled with a low flow melt index.

After use, the container may be returned to a central collection point. At this collection point the lid is forcibly removed from the cup resulting in damage to

either the cup or lid. Any liquid remaining in the cup is discarded and the plastic components of the assembly are recycled.

Whilst the embodiment of the invention described herein includes an aperture in the form of a straw it is not limited to this arrangement.

Any reference to prior art contained herein is not to be taken as an admission that the information is common general knowledge, unless otherwise indicated.

10 Finally, it is to be appreciated that various alterations or additions may be made to the parts previously described without departing from the spirit or ambit of the present invention.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

A drinking apparatus including:

 a container having a lid and defining an internal cavity for holding a body of liquid;
 a valve element operates in conjunction with an opening on the container and is operable between an open condition and a closed condition;

 the valve element is biased to the closed condition wherein the apparatus completely encapsulates the internal cavity to thereby prevent substances from being introduced to the cavity; and removal of the lid from the container results in an indication that

the apparatus has been tampered with.

2. A drinking apparatus according to claim 1 wherein the action of drawing liquid through the opening causes the valve element to move to the open condition.


20


- 3. A drinking apparatus according to either claim 1 or claim 2 wherein the valve element is biased to the closed condition by gravity.
- 25 4. A drinking apparatus according to any preceding claim wherein the container is a cup.
- 5. A drinking container according to any preceding claim wherein the lid is arranged to be snap fitted to the container.
 - 6. A drinking apparatus according to any preceding claim wherein the lid and container fit together closely to


resist removal of the lid by use of a leveraging tool.

- 7. A drinking apparatus according to any preceding claim
 5 wherein the opening is the bore of a straw.
 - 8. A drinking apparatus according to claim 7 wherein the straw is marked on its outer surface in the region of the valve element.

- 9. A drinking apparatus according to claim 8 wherein the region of the straw is marked by colouring the region.
- 15 10. A drinking apparatus according to claim 9 wherein the region of the straw is marked by being fluorescent or luminous.
- 11. A drinking apparatus according to any preceding claim wherein the valve element is luminous or fluorescent.
- 12. A drinking apparatus according to any preceding claim wherein the indication that the apparatus has been tampered with includes damage to either the lid or the cup.










<u>FIG.5</u>

*FIG.*4









International application No.

PCT/AU03/01016

| A. | CLASSIFICATION OF SUBJECT MATTER | R | | | | | | | |
|---|--|---|--|---------------|--|--|--|--|--|
| Int. Cl. 7: | A47G 21/18, 19/22, 19/12. | | | | | | | | |
| According to | International Patent Classification (IPC) or to bo | th 1 | national classification and IPC | | | | | | |
| B. FIELDS SEARCHED | | | | | | | | | |
| Minimum documentation searched (classification system followed by classification symbols) IPC A47G 21/18, 19/22, 19/12, A61J 15/00. | | | | | | | | | |
| Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched AU IPC A47G 21/18, 19/22, 19/12, A61J 15/00. | | | | | | | | | |
| Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) DWPI (A47G 21/18, 19/22, 19/12, A61J 15/00) AND ((TAMPER+) OR (STRAW+) OR (SPIK+) OR(DRUG+ OR POISON+ OR ALCOHOL+)) | | | | | | | | | |
| C. DOCUMENTS CONSIDERED TO BE RELEVANT | | | | | | | | | |
| Category* | Citation of document, with indication, where a | Relevant to claim No. | | | | | | | |
| A A A | WO 0049920 A (STICHTING VAN DE OMANAGEMENT TRUST) 31 August 200 See entire document. WO 0049922 A (DARK) 31 August 2000 See entire document. WO 9938423 A (CANNON RUBBER LESSEE entire document. | · | · | | | | | | |
| X Further documents are listed in the continuation of Box C X See patent family annex | | | | | | | | | |
| * Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "B" later document published after the international filing dat and not in conflict with the application but cited to under or theory underlying the invention "X" document of particular relevance: the claimed invention | | | | | | | | | |
| after the | after the international filing date co | | ocument of particular relevance; the claimed invention cannot be onsidered novel or cannot be considered to involve an inventive step then the document is taken alone | | | | | | |
| claim(s) or which is cited to establish the cor publication date of another citation or other special wit reason (as specified) a p | | note that the companion of particular relevance; the claimed invention cannot be a nisidered to involve an inventive step when the document is combined the one or more other such documents, such combination being obvious to person skilled in the art | | | | | | | |
| exhibiti "P" docume | exhibition or other means | | | | | | | | |
| Date of the actual completion of the international search 19 September 2003 | | Date of mailing of the international search report | 2 4 SEP 2003 | | | | | | |
| Name and mailing address of the ISA/AU | | Authorized officer | | | | | | | |
| AUSTRALIAN PATENT OFFICE PO BOX 200, WODEN ACT 2606, AUSTRALIA E-mail address: pct@ipaustralia.gov.au Facsimile No. (02) 6285 3929 | | R. WEBER Telephone No: (02) 6283 2546 | | | | | | | |
| | | | | _ | | | | | |



INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU03/01016

| C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT | | | | | | |
|---|---|-----------------------|--|--|--|--|
| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. | | | | |
| A | WO 0170079 A (SAFETY 1 ST INC) 27 September 2001. See entire document. GB 2314497 A (ANTONIOU) 7 January 1998. | | | | | |
| Α | See entire document. US 6427864 B (ASSELIN) 6 August 2002. | | | | | |
| Α | See entire document. DE 10158369 A (GATTINGER) 12 June 2003. | | | | | |
| A,E | See entire document. EP 266067 A (KOSA DESIGNS LIMITED) 4 May 1988. | | | | | |
| Α | See entire document. | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |



International application No. PCT/AU03/01016

Information on patent family members

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

| Patent Document Cited in Search Report | | Patent Family Member | | | | | | |
|---|-----------|----------------------|----------|----|-----------|------|--------------|--|
| wo | 200049920 | AU | 34246/00 | DE | 19907581 | | | |
| wo | 200049922 | AU | 30026/00 | BR | 200008547 | EP | 1154713 | |
| | | US | 6116458 | | | | | |
| wo | 9938423 | AU | 22913/99 | EP | 1051094 | GB | 2333770 | |
| | | NZ | 505906 | PL | 342039 | US . | 6305570 | |
| wo | 200170079 | AU | 45597/01 | EP | 1265517 | US | 6568557 | |
| GB | 2314497 | NIL | | | | | | |
| US | 6427864 | NIL | | | | | | |
| DE | 10158369 | NIL | | | | • | | |
| EP | 266067 | AU | 79346/87 | | | | | |
| | | | | | | | END OF ANNEX | |